

Links

Standard

Feature: 2-hole Standard type has selectable and configurable dimension options.

Links - Standard

L Selectable Type	D ₂ Configurable	W Configurable	Type R	Material	Surface Treatment
LNSB	LNDB	LNFB	LNFRB	1045 Carbon Steel or Equivalent*	Black Oxide
—	LNDM	LNFM	LNFRM	—	Electroless Nickel Plating
LNSS	LNDS	LNFS	LNFRS	304 Stainless Steel	—

*1018 Carbon Steel or Equivalent for T=2.

L Selectable

D₂ Configurable

W Configurable

Type R

T Dimension Tolerance

T	2	3-16	19-22
±0.15	0	0	-0.33
	-0.3		

L Selectable

Type	D _{H7}	L Selection					W	T	ℓ	C		
		25	30	40	50	75						
LNSB LNSS	5	25	30	40	50	13	5	L+13	3			
	6	25	30	35	40					45	50	75
	8	25	30	35	40					45	50	75
	10	30	40	50	75					16	L+16	
	12	50	75	19	9	L+19	5					

D₂ Configurable

Type	D _{H7}	D _{2H7} 1 mm Increment	L 1 mm Increment	T		W	ℓ	F	C		
				2	3						
LNDB LNDM LNDS	2	2-20 D ₁ ≥D ₂ ⊕ When D _{2H7} =2, T≤9	5-75	2	3	8	L+8	4	2		
	3		5-150	5	6						
	4		6-150	5	6					9	
	5		7-150	5	6	9	13	L+10	5	3	
	6		8-150	5	6	9					
	8		10-150	5	6	9					
	10		12-200	5	6	9	16	L+12	6	5	
	12		14-200	5	6	9					12
	13		15-200	5	6	9					12
	14		16-200	5	6	9	12	19	L+16	8	8
	15		18-200	5	6	9	12				
	16		20-200	5	6	9	12				
	18		22-200	9	12	16	25	L+18	9	5	
	20		25-300	9	12	16					19
	25		30-300	9	12	16					19

Links

Standard, continued

W Configurable

Part Number Type	D _{H7}	L 1 mm Increment	W 1 mm Increment	T					ℓ	C			
				2	3	5	6	9					
LNFB LNFM LNFS	2	10-75	7-12	2	3	L+8	2						
	3			5	6								
	4	10-150	10-20	5	6			9	L+10	3			
	5			5	6			9					
	6			5	6			9					
	8			5	6			9			10		
	10	20-200	15-30	5	6			9	10	L+12	5		
	12			20-30	5			6	9			10	12
	13		5		6			9	10			12	16
	14		20-40		9			10	12			16	
	15				9			10	12			16	
	16				9			10	12			16	
	18				9			10	12			16	
	20		30-300	25-50	9			10	12			16	19
	25	30-60			9			10	12	16	19	22	L+50

Type R

Part Number Type	D _{H7}	D _{2H7} 1 mm Increment	L 1 mm Increment	W 1 mm Increment	T					F	R		
					2	3	5	6	9				
LNFRB LNFRM LNFRS	2	2-20 D ₁ ≥D ₂ ⊕ When D _{2H7} =2, T≤10	20-75	6-12	2	3	W/2	W/2					
	3				5	6							
	4		20-150	7-20	5	6			W/2	W/2			
	5			8-20	5	6					9		
	6			9-20	5	6					9		
	8			10-20	5	6					9		
	10		30-200	12-20	5	6			9	10	W/2	W/2	
	12			16-30	5	6			9	10			
	13			18-30	9	10			12	16			
	14			19-30	9	10			12	16			
	15			20-40	9	10			12	16			
	16			21-40	9	10			12	16			
	18			22-40	9	10			12	16			
	20			24-40	9	10			12	16			
	25		40-300	30-50	9	10			12	16	19	L+36	8
	25			35-60	9	10			12	16	19		



Part Number Example

Part Number - D₂ - L - W - T

LNSB5 - L25 - T6

LNDB10 - 8 - L100 - T6

LNFB10 - L60 - W20 - T9

LNFRB8 - 6 - L100 - W15 - T9



Part Number Alterations

Part Number - D₂ - L (LC) - W - T

LNFB10 - LC100.5 - W20 - T9

Alteration	Code	Spec.
	LC	L dimension in 0.1 mm increment. Specify LC instead of L. Ordering Code: LC100.5 ⊗ Not available for L Selectable Type